

IN THE SPECIFICATION:

Please amend the specification as follows:

Paragraph beginning on page 4, at prenumbered line 7, has been amended as follows:

Figs. ~~3(a)-3(c)~~ 3(a)-3(b) which respectively shows a top view, side view and bottom view of the fuse seat in accordance with one embodiment of the present invention.

Paragraph beginning on page 6, at prenumbered line 8, has been amended as follows:

Referring to Figs. ~~3(a)-3(c)~~ 3(a)-3(b), which respectively shows a top view, side view and bottom view of the fuse seat 40 in accordance with one embodiment of the present invention. As shown in Figs. ~~3(a)-3(c)~~ 3(a)-3(b), the fuse seat 40 of the present invention is positioned inside the space 11 and beside the second conductive plate 30, which comprises a third containing slot 41 and a fourth containing slot 45, wherein, the third containing slot 41 is used to contain and fix a second end of said fuse 70, and said fourth containing slot 45 is used to contain and fix a second conductive wire 62 of said power cable 60. The third containing slot 41 is a U-shaped, and extends forward from the approximately central of the U-shaped bottom to form a U-shaped fourth containing slot 45, and two walls of said fourth containing slot 45 respectively has a opening 46, thus, each walls of said fourth containing slot 45 respectively has a first clip 47 and a second clip 48 so as to fasten said second conductive wire 62 of said power cable 60 by said first clip 47 and second clip 48. Furthermore, the widths of said first containing slot, second containing slot and third containing slot are about and bigger than the width of said fourth containing slot 45.